## Hydraulic System Mineral Oil

***Jaguar Hydraulic Fluid***

DESCRIPTION

Castrol Hydraulic System Mineral Oil (Jaguar) is specially formulated for use in hydraulic systems where a mineral oil is specified.

APPLICATION

Castrol Hydraulic System Mineral Oil (Jaguar) is for use in the suspension levelling systems of Jaguar cars. It should never be mixed with conventional synthetic brake fluids or used where these fluids are recommended.

| FEATURES | BENEFITS |
|---|---|
| S High viscosity index | S Viscosity remains relatively constant under normal operating conditions |
| S Very shear stable | S Retains viscosity profile throughout life of the oil |
| S Fully compatible with all elastomers currently in use in automotive hydraulic systems | S No need to change seals |

PERFORMANCE

Girling TS2-31-03

Ford ESN-M6C59-A

TYPICAL CHARACTERISTICS

Relative Density @ 20º C 0.850
Viscosity @ 40º C, cSt 19.8
Viscosity @ 100º C, cSt 6.0
Flash Point º C 120
Pour Point º C -58
Viscosity Index 285

**Health, Safety and Environment; Health, Safety and Environment**

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products. ; Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.
Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.; Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

---

**Typical Characteristics ; Typical Characteristics**

---

| | **Test Methods; Test Methods** | **Units; Units** | **Value: ; Value:** |
|---|---|---|---|

---

---

*The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.; The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.*

**This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.; This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.**
**It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.; It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.**

**The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).; The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).**

Castrol (UK) Ltd
Witan Gate House Lubricants Helpline: 01908 853133
500/600 Witan Gate
MILTON KEYNES
MK9 1ES; Castrol (UK) Ltd
Witan Gate House Lubricants Helpline: 01908 853133
500/600 Witan Gate
MILTON KEYNES
MK9 1ES

---

Date Created: 10/10/2002 Last Modified:04/10/2005